
RELEASE NOTES FOR GENOMES PROCESSED USING COMPLETE GENOMICS SOFTWARE VERSION 1.7.3.

CONTENTS

New features and enhancements.....	1
Changes to version 1.7.2	1
Changes to version 1.7.1	2
Changes to version 1.6	4
Changes to version 1.5	4
Changes to version 1.4	5

Customers should consult the DataFileFormats.pdf file corresponding to any data set for information specific to those data. Customers can check the header information in the files to determine which version of CGI documentation applies.

NEW FEATURES AND ENHANCEMENTS

The following new features and enhancements are provided in this release by comparison with previous data shipped or released by Complete Genomics:

1. We are no longer including output from our beta-CNV algorithm (introduced in 1.7.1) as we continue development, validation and performance tuning of those methods. We expect to release an updated version in the near future.

CHANGES TO VERSION 1.7.2

1. We have added a new field to the evidenceDnb file (FileNumLane) to make it easier for customers to link reads and mappings to records in the evidence files. This does mean that any programs written to parse the evidenceDnb file will need to be changed.
2. We have added a new calculation to the coverageRefScore file (weightSumSequenceCoverage) that reflects coverage of each base in the reference genome factoring in reads which may not map uniquely. This is by contrast with the unique sequence coverage previously and still included in the coverageRefScore file. We find that the weighted-sum metric is best used in quantitative copy number calculations,

Complete Genomics data is for Research Use Only and not for use in the treatment or diagnosis of any human subject.

support@completegenomics.com

Information, descriptions and specifications in this publication are subject to change without notice.

© Complete Genomics, Inc., 2010

Published in U.S.A., April 2010

for example. It also reflects many reads which can be recruited into de novo assembly. However, please do recall that both of these metrics are computed prior to assembly, and reflect the initial rather than final determination of read placements.

3. We have removed the DOC (documentation) directory from the customer deliverable. In previous versions, the DataFileFormat.pdf was included in the DOC directory. This document is now available from support@completegenomics.com.
4. The documentation has been updated and the data format version number has been incremented to 1.1 to reflect the changes above.

CHANGES TO VERSION 1.7.1

These changes appeared in version 1.7.1 data releases by comparison with earlier versions.

1. We added a gene variation summary report (for example: gene-var-summary-GS19240-ASM.tsv.gz) in the ASM folder. For each protein-coding gene, this file summarizes the numbers of variations with certain functional impacts (counts of nonsynonymous SNPs, possible frameshifts, etc.).
2. We added a **BETA** quantitative copy number (CNV) computation. The quality of these CNV calls has not yet been extensively validated, and the exact performance in terms of sensitivity and specificity remains under study. However we believe these initial results may be of use to customers. We will likely modify the CNV calculation over time as we continually improve it, and we request customer feedback on these beta results.
 - o Currently, CNV calls are based solely on increases or decreases in mapping rates (mapped coverage) normalized by various factors. Due to fluctuation in coverage owing to phenomena other than CNVs, results are currently limited to putative copy number changes affecting regions of approximately 20kb or more. CNV reporting is provided in two tab-separated tables – the CNV segmentation table and the CNV details table. Supporting evidence for these CNV calls is provided via mappings and coverage data provided in other files.
 1. CNV segmentation table: Provides a segmentation of the complete reference genome into regions of various ploidy levels, giving the estimated ploidy, the average adjusted coverage for each segment, and measures of confidence in the called segments.
 2. CNV details table: Provides information on estimated ploidy every 2kb along the genome, giving average coverage and details regarding the estimated likelihood of each of various possible ploidy levels.
3. Several file format improvements were made from previous versions.
 - o We renamed the variation types ref-consistent and ref-inconsistent. There is no change to semantics of each variation type, although by changing the name we wish to highlight the fact that these represent cases where the assembler was not able to fully resolve the allele sequence:

1. Ref-consistent was renamed to no-call-rc (no-call reference consistent) – where one or more bases are ambiguous, but the allele is potentially consistent with the reference.
2. Ref-inconsistent was renamed to no-call-ri (no-call reference inconsistent), where one or more bases are ambiguous, but the allele is definitely inconsistent with the reference.
 - We renamed homozygous reference calls to “ref” rather than “=”, although “=” continues to indicate the reference allele in these ref-called regions.
 - We updated the headers of the variation and annotation files to include a reference to the specific version of the external reference data source used e.g. dbSNP version, Genome Reference sequence (and RefSeq gene annotations) used, etc.
 - We changed a number of file names to ensure that all files get unique names within an assembly and between samples, so they remain unique even if files are moved. This provides customers more convenience if they wish to reorganize the data hierarchy or gather various data subsets.
 - The “chunk” numbers appended onto the mapping and reads files now have leading zeros (“_001” for example).
 - We removed a column in the Summary file describing the score threshold set used. Genomes produced using a specific version of the CGI pipeline always use the same threshold set, and only one set (this has been true for some time) so this column was extraneous. Technical documentation we are preparing on the analysis process will describe these thresholds in a more user-friendly way.
 - We renamed some of fields in the file headers for clarity.
 1. #BUILD to #SOFTWARE_VERSION
 2. #VERSION to #FORMAT_VERSION
 - We fixed a minor bug where the “=” allele was not always output in the corresponding column of the variations file in haploid regions. This bug did not affect the results, only the exact syntax of how such calls were reported.
4. We added empirically measured gap information, per library, in a set of new files included in the LIB folder. In that folder is one directory per library, and one set of files per library directory (normally, a genome is sequenced from a single library in Complete Genomics’ current process). Gap distribution information is useful for mapping, assembly and variant calling of the read data. It is also useful in discordant paired-end analyses to look for putative structural variants. Note that these new data files replace the lib_* files previously included in the MAP folder subdirectories.
5. All data files except readme.txt and Data File Format.PDF are now compressed using bzip2 (.bz2 extensions) rather than gzip (.gz extensions). Customers should be aware that bzip2 can be slower at decompressing than gzip, however the space savings and improved file transfer times were considered helpful by many.
6. The file format version number has been incremented to 1.0 to reflect these changes. We recommend that any code customers or partners write should check this number on any data file(s) read to ensure that the program is compatible with the data file(s).

7. The README.txt and DataFileFormats.PDF document have been updated to reflect the changes above. We have also added this release notes file.

CHANGES TO VERSION 1.6

These changes appeared in version 1.6 data releases by comparison with earlier versions.

1. Mapping and reads files in the subdirectories of the MAP folder have been broken into “chunks” in order to keep their sizes <5GB per file. This allows compatibility with storage systems (such as certain cloud storage providers) for which 5GB is an upper file size limit.
 - To accomplish this, we limit the number of reads described in any one mapping+reads file pair to 30 million. Mapping and reads files remain paired 1:1, and numbers are appended on the end of the mappings and reads files (such as “_1”, “_2”, “_3”) to indicate the files which should be processed together.
 - The offset indexes of reads provided in the evidenceDNB files now have a particular interpretation. When this number is less than 30,000,000 the reads are in the first chunk (eg the mapping and reads files with “_1”) at this 0-based position (data line) in that file. When the number is 30,000,000 to 59,999,999, the reads are in the second chunk (“_2”), with an offset position in that file of 30,000,000 less than the index provided. When the number is greater than 60 million, the reads are in the third chunk and 60M should be subtracted from the index to get the position, etc.
2. Subdirectories of the MAP folder are now named by slide and lane, rather than by an arbitrary mapping job number. This makes it easier to find reads and mappings based on knowing the slide and lane information, such as is used in the evidenceDNB files.
3. Previously, reads were filtered (not stringently) before inclusion into a customer data set. The stringency of these filters has been further reduced as we find doing so provides additional information that can improve accuracy of some variant calls without a significant impact on false positives. Furthermore, providing a more complete set of reads can facilitate reanalysis of the read-level data using various methods. As a consequence, customers should expect to see somewhat lower rates of mappability as these additional reads are included – the rate has not actually gone down just the number of non-mapping reads included has increased.
4. Updates to documentation accordingly.

CHANGES TO VERSION 1.5

Changes in 1.5 by comparison with earlier data releases.

1. Improvements were made in the variant calling algorithm that provide better accuracy of calls in duplicated regions and low copy number repeats. The variant scores now factor in uniqueness of evidence to further reduce false positives in such regions. Customers can consult the correlation file in the EVIDENCE folder to the underlying scores used in this calculation.
2. The assemblies and read alignments underlying all called variant regions are now provided in the EVIDENCE folder.
3. Updates to documentation accordingly.

CHANGES TO VERSION 1.4

Changes in 1.4 by comparison with earlier data releases.

Numerous changes were made between version 1.3.x of the CGI software, as used in our data submitted to SRA as part of the Drmanac et al. publication (*Science*, Jan 2010 print edition). Among other changes, the C++ API is no longer required nor usable. Customers can contact support@completegenomics.com for further information.